


Highly precise and efficient top solid indexable drill

# TPDB Plus Drill

(TPDB Plus/TPDB-F<sup>new</sup>/TPDB-H<sup>new</sup>)

KORLOY  
TECH-NEWS



- Increased productivity with stable machining.
- Optimized flute design and excellent chip evacuation ensure high quality of hole condition.
- TPDB Plus Drill is available for machining of variously shaped surfaces and steel structure frames.

Highly precise and efficient top solid indexable drill

# TPDB Plus Drill

To obtain better work efficiency, excellent machining performance and reduced cutting time are always in need for various industries. Thus, the demands for efficient cutting tools are steadily increasing.

KORLOY newly launched high quality and efficient indexable drill, TPDB Plus Drill in accordance with the market's needs.

**TPDB Plus** implemented high helix flute, which enhanced chip evacuation, and it leads to higher qualified machining with surface finish of hole and roundness.

In addition, TPDB-F for drilling various workpiece with various shaped surfaces and TPDB-H, an

exclusive indexable drill for drilling steel structural frame are launched for various industries.

TPDB-F is available for drilling of angled surface, curved surface drilling, plunging and boring. It is suitable for drilling flat bottom and drilling pilot hole. In addition, by using the least tools, it reduces the time for tool exchanging and cycle time as well.

The TPDB-H insert, with its exclusive low cutting resistance cutting edge design enhancing centering, reduces cutting load and increases quality of hole condition. Its high helix angled flutes also devote to improve machining stability and productivity by preventing chip jamming which causes chattering nor unexpected breakage.



## Excellent machinability


- Fine drilling performance with exclusive edge per application
- Enhanced chip evacuation with high helix angle

## Increased productivity

- Reduced cycle time by using the least tools (TPDB-F)
- High durability due to special surface treatment

# TPDB Plus

## Application range



Tools	Application range					
	Drill Diameter (Ø)	Aspect ratio (L/D)	Tolerance of drill dia.	Tolerance of hole	Surface finish of hole (Ra)	Workpiece material
TPDB Plus	10-32.99 mm	3, 5, 8, 10, 12	h7	IT10	≤ 2.0 μm	P, K

## Applicable industries

Generation of wind and nuclear power	Shipbuilding	Railway and construction	Aircraft	Automobile

## Code system

### 【Holder】

<b>TPD</b>	<b>B</b>	<b>200</b>	-	<b>25</b>	-	<b>5</b>	-	<b>P</b>
Top solid Piercing Drill	Insert type B: Blade type	Drill dia. 200: Ø20.0		Shank dia. 25: Ø25		Aspect ratio (L/D) 3D, 5D, 8D, 10D, 12D		Plus

### 【Insert】

<b>TPD</b>	<b>200</b>	<b>B</b>
Top solid Piercing Drill	Drill dia. 200: Ø20.0	Insert type B: Blade type


## Features

- **Highly precise clamping system** - Superior clamping precision with auto-centering system and highly precise grinding clamping parts
- **Screw on clamping system** - Easy to replace inserts
- **Sharp cutting edge** - Low cutting load and good chip control
- **Holder with excellent durability** - Holder with high rigidity and excellent wear resistance due to special surface treatment
- **Holder with excellent chip control** - Low cutting resistance and outstanding chip evaluation by applying high helix angle



# Indexable drill selection guide

— TPDB Plus    — TPDC Plus Drill    — King Drill



## TPDB Plus <sup>new</sup>

- Good surface finish
- High productivity
- 3D, 5D, 8D, 10D, 12D



## TPDC Plus Drill <sup>new</sup>

- One step clamping
- High precision of hole
- 1.5D, 3D, 5D, 8D, 10D, 12D



## King Drill


- 4 corners (central and peripheral)
- 2D, 3D, 4D, 5D



Tools	Drill dia.	Aspect ratio	Cost	Productivity	Precision of hole	Surface finish
TPDB Plus <sup>new</sup>	★★★	★★★★	★★★	★★★★	★★★	★★★★
TPDC Plus Drill <sup>new</sup>	★★	★★★★	★★	★★★★	★★★★	★★★★
King Drill	★★★★	★★	★★★★	★★	★★	★★★

## Run-out


- **Workpiece** Alloy steel (42CrMo4)
- **Cutting conditions**
  - vc (m/min) = 90
  - fn (mm/rev) = 0.25
  - ap (mm) = 120
  - wet (20 bar)
- **Tools**
  - Insert** TPD250B (PC5300)
  - Holder** TPDB250-32-5-P (Drill dia. = Ø25 mm)



# Performance evaluation

## Cutting load

- **Workpiece** Alloy steel (42CrMo4)
- **Cutting conditions**  $vc$  (m/min) = 120,  $f_n$  (mm/rev) = 0.25,  $a_p$  (mm) = 120, wet (20 bar)
- **Tools** **Insert** TPD250B(PC5300) **Holder** TPDB250-32-5-P (Drill dia. = Ø25 mm)



- **TPDB Plus**  
Average thrust 4998N
- **Competitor**  
Average thrust 5492N

## Surface finish

- **Workpiece** Alloy steel (42CrMo4)
- **Cutting conditions**  $vc$  (m/min) = 120,  $f_n$  (mm/rev) = 0.35,  $a_p$  (mm) = 120, wet (20 bar)
- **Tools** **Insert** TPD250B (PC5300) **Holder** TPDB250-32-5-P (Drill dia. = Ø25 mm)



[ TPDB Plus ]  
Ra = 0.54  $\mu\text{m}$



[ Competitor ]  
Ra = 0.57  $\mu\text{m}$

## Chip control

- **Workpiece** Alloy steel (42CrMo4)
- **Cutting conditions**  $vc$  (m/min) = 120,  $f_n$  (mm/rev) = 0.35,  $a_p$  (mm) = 120, wet (20 bar)
- **Tools** **Insert** TPD250B (PC5300) **Holder** TPDB250-32-5-P (Drill dia. = Ø25 mm)



[ TPDB Plus ]





[ Competitor ]

# Performance evaluation

## Precision

- **Workpiece** Alloy steel (42CrMo4)
- **Cutting conditions**  $vc$  (m/min) = 90/120,  $fn$  (mm/rev) = 0.25/0.35,  $ap$  (mm) = 120, wet (20 bar)
- **Tools**
  - Insert** TPD250B (PC5300)
  - Holder** TPDB250-32-5-P (Drill dia. = Ø25 mm)




## Wear resistance

- **Workpiece** Alloy steel (42CrMo4)
- **Cutting conditions**  $vc$  (m/min) = 100,  $fn$  (mm/rev) = 0.3,  $ap$  (mm) = 100, wet (30 bar)
- **Tools**
  - Insert** TPD250B (PC5300)
  - Holder** TPDB250-32-5-P (Drill dia. = Ø25 mm)



[ TPDB Plus ]




[ Competitor ]

- ▶ Improved built up edge and chipping resistance lead stable wear on TPDB Plus insert's edge and obtain longer Max. tool life.

- **Workpiece** Carbon steel (C45)
- **Cutting conditions**  $vc$  (m/min) = 100,  $fn$  (mm/rev) = 0.3,  $ap$  (mm) = 100, wet (30 bar)
- **Tools**
  - Insert** TPD250B (PC5335)
  - Holder** TPDB250-32-5-P (Drill dia. = Ø25 mm)




[ TPDB Plus ]



[ Competitor ]


- ▶ Sharper cutting edge than competitor's improves built up edge resistance and tool life.

## Grade features




### PC5300

- Applying PVD coating with high hardness and stability in machining at high temperature
- Stable drilling due to high cutting edge strength and excellent chipping resistance
- Optimal grade for drilling alloy steel and cast iron



### PC5335

- Applying PVD coating with high toughness and excellent lubrication
- Coating layer highly adhering to substrate
- Optimal grade for general structural carbon steel (FE360B, etc.) and machine structural carbon steel (C45, etc.) machining



### PC330P

- Applying PVD coating with high surface finish and excellent lubrication
- Coating layer with excellent hardness at high temperature and oxidation resistance
- Optimal grade for welding structural carbon steel (E355DD, etc.)

## Recommended cutting conditions

Workpiece			Grade	vc (m/min)	Aspect ratio (L/D) = 3D, 5D Feed rate (mm/rev) per drill dia. (mm)		
ISO	Workpiece materials	HB			Ø10 - Ø16.9	Ø17 - Ø26.9	Ø27 - Ø32.9
P Carbon steel	Low carbon steel	80 - 120	PC5335 PC330P	110 (80-140)	0.15 - 0.30	0.20 - 0.35	0.25 - 0.40
	High carbon steel	180 - 280	PC5335 PC330P	100 (70-130)	0.15 - 0.30	0.20 - 0.35	0.25 - 0.40
P Alloy steel	Low alloy steel	140 - 260	PC5300	110 (80-140)	0.18 - 0.35	0.23 - 0.38	0.28 - 0.43
	Low alloy heat treated steel	200 - 400	PC5300	75 (50-100)	0.18 - 0.35	0.23 - 0.38	0.28 - 0.43
	High alloy steel	50 - 260	PC5300	70 (50-90)	0.18 - 0.30	0.20 - 0.35	0.25 - 0.40
	High alloy heat treated steel	220 - 450	PC5300	60 (40-80)	0.18 - 0.30	0.20 - 0.35	0.25 - 0.40
K Cast iron	Gray cast iron	150 - 230	PC5300	110 (80-140)	0.18 - 0.35	0.20 - 0.40	0.25 - 0.45
	Ductile cast iron	160 - 260	PC5300	100 (70-130)	0.18 - 0.35	0.20 - 0.40	0.25 - 0.45


※ In case of 8D, machine in 20-30% lower cutting conditions than the mentioned above, or machine the beginning of hole (1.5D) before drilling.

※ In interrupted machining, reduce the feed to 0.1-0.15 machining around the interrupted part.

※ Refer to the 'Recommended drilling method' on the page 10 for drilling of 10D -12D.


## Recommended drilling method (10D, 12D)

### Machine a pilot hole (with a pilot drill)



- Machine a pilot hole with the depth of cut as 0.5D and at 30% lower speed using a 1.5D or 3D drill.

### Start drilling



- After machining the pilot hole, replace the pilot drill to a drill for further operation and machine in recommended cutting conditions.



Result of general drilling



Result of recommended drilling

Good surface finish


## Precaution in drilling

### Angled surface drilling



- The approach angle between drill and the workpiece at the beginning and the end should be less than 6°.
- Reduce the feed (fn) to 30-50% than general cutting conditions at the beginning and the end of angled surface.

### Stacked plates drilling




- Gap between the plates could make wrong chip evacuation causing fracture of the drill.
- Place stacked plates without any gap between each.

### Plunging



- Irregular cutting resistance in plunging could cause fracture and deformation of the drill.

### Boring



- Boring is not recommended due to wear and chipping in the corner of the insert.

## How to clamp an insert

### Clamping an insert to a holder



[Pic.1]

- ① Put an insert on the tip seat of the holder.
- ② As the [Pic.1], push the insert to the v-shaped groove of the holder.
- ③ Screw and clamp the insert.

### Changing the used insert to a new one



[Pic.2]



[Pic.3]


- ① Unscrew and separate the used insert from the holder.
- ② As the [Pic.2], clean the insert seat.
- ③ Put a new insert on the tip seat.
- ④ As the [Pic.3], clamp the insert pushing it with a hand not to separate from the holder.

## Check point in drilling




- Condition of the clamped workpiece
- Revolution of the main axis of the machine
- Condition of the holder
- Run-out of the clamped drill (Max. 0.03 mm)
- Condition of supplying coolant (pressure, flow, concentration)
- Chip evacuation

## Supply of coolant



- Supply enough coolant to the beginning of the hole.
- Minimum pressure of oil coolant: 5 bar
- Minimum flow of coolant: 5 l/min






## Replacement of holders and screws

Worn part	How to check	Description
<p>[Pic.1]</p> 	<p>[Pic.2]</p> <p>Check the gap</p> 	<ul style="list-style-type: none"> <li>• In case of drilling for a long time as shown in the [Pic.1] the 'A' part is torn and twisted due to torque.</li> <li>• As shown in the [Pic.2] check the gap between the insert and the tip seat turning the clamped insert from side to side. If there is a gap between them, replace the used holder to a new one.</li> </ul>
<p>[Pic.3]</p> 	<p>[Pic.4]</p> <p>Check the moving</p> 	<ul style="list-style-type: none"> <li>• The insert could move up or down due to the load on the Z-axis in drilling over an extended period of time which causes wear on the 'B' part as shown the [Pic.3].</li> <li>• After clamping an insert, if the insert is moving or there is a gap between the insert and the tip seat as shown in the [Pic.4] replace the used holder to a new one.</li> </ul>
<p>[Pic.5]</p> 	<p>[Pic.6]</p> <p>Check the moving</p> 	<ul style="list-style-type: none"> <li>• After an extended period of use, the screw can be worn as shown in the 'E' part of [Pic.5] which could decrease the clamping force of the insert. When the screw is worn, replace the old screw to a new one among the enclosed extras.</li> <li>• Spreading the grease on the screw makes it last longer.</li> </ul>
<p>[Pic.6]</p> <ol style="list-style-type: none"> <li>① Check the 'C' and 'D' parts as shown in the [Pic.6]</li> <li>② Check whether the chips are getting longer or not.</li> </ol>		<ul style="list-style-type: none"> <li>• Winding or jamming of long and tiny chips in drilling causes wear or scratch on the 'C' part as shown in the [Pic.6] due to chattering from machining in improper cutting conditions. In that case, reset the cutting conditions and check the Run-out before machining.</li> <li>• The excessive wear of the part 'D' as shown in the [Pic.6] relating to chip curling might cause long chips.</li> </ul>

## Types of damage to drill and solutions

Scratches on the margin		
	<b>Factors</b>	<ul style="list-style-type: none"> <li>• Lack of coolant lubrication</li> <li>• Lack of coolant in deep drilling due to MQL system</li> <li>• Bend of drill due to improperly placed holder or using a long holder</li> <li>• Low rigidity or large concentricity</li> </ul>
	<b>Solutions</b>	<ul style="list-style-type: none"> <li>• Use more coolant.</li> <li>• Place workpiece tightly and check the concentricity.</li> <li>• Check the precision of installment of drill. (below 0.03 mm)</li> <li>• Reduce the cutting speed.</li> </ul>
Wear on the margin		
	<b>Factors</b>	<ul style="list-style-type: none"> <li>• Due to machining pure metal or heat resisting alloy</li> <li>• Less back taper due to using a holder for a long time</li> <li>• Unstable machining at the end of hole due to interruption</li> <li>• Lack of coolant lubrication on the peripheral section of holder contacting workpiece</li> </ul>
	<b>Solutions</b>	<ul style="list-style-type: none"> <li>• Set up proper tool life and manage its usage.</li> <li>• Check the shape of machining part.</li> <li>• Check the kind and concentration of coolant.</li> </ul>
Chipping on the corner		
	<b>Factors</b>	<ul style="list-style-type: none"> <li>• Interrupted machining (End of hole is inclined or curved shape, junction hole in the middle of hole.)</li> <li>• Chattering in drilling due to unstable clamping, low rigidity of machine or bending of drill</li> <li>• Chattering due to unstable clamping of drill</li> </ul>
	<b>Solutions</b>	<ul style="list-style-type: none"> <li>• Check the part of machining.</li> <li>• Machine in lower cutting speed.</li> <li>• Place workpiece tightly.</li> <li>• Check the performance of the machine.</li> <li>• Check the precision of installment of drill. (below 0.03 mm)</li> </ul>
Wear on the rake face		
	<b>Factors</b>	<ul style="list-style-type: none"> <li>• Low cutting speed</li> <li>• Machining free-cutting steel</li> <li>• Erosion of chip and flute</li> <li>• Lack of coolant lubrication</li> </ul>
	<b>Solutions</b>	<ul style="list-style-type: none"> <li>• Increase cutting speed.</li> <li>• Set a lower thinning angle.</li> <li>• Reduce the honing.</li> <li>• Use more coolant.</li> </ul>
Chipping on the rake face		
	<b>Factors</b>	<ul style="list-style-type: none"> <li>• Fracture on the cutting edge partially due to pre-treatment on the center of hole</li> <li>• Unstable chip evacuation due to step drilling and external coolant</li> <li>• Chattering in drilling and low precision of holder installment</li> </ul>
	<b>Solutions</b>	<ul style="list-style-type: none"> <li>• Check if there is pre-machining or not.</li> <li>• It is recommended to use internal coolant in step drilling.</li> <li>• Check the state of clamping workpiece and the precision of drill installment. (below 0.03 mm)</li> </ul>

## Types of damage to workpiece and check points






Poor surface finish (rough, scratch, etc.)		
	<b>Factors</b>	<ul style="list-style-type: none"> <li>• Low rigidity of machine and improperly clamped workpiece</li> <li>• Large concentricity and lack of coolant</li> </ul>
	<b>Solutions</b>	<ul style="list-style-type: none"> <li>• Clamp the workpiece properly and check the concentricity.</li> <li>• Increase the amount and pressure of coolant</li> </ul>
Remained lots of burr at the end of the drilled hole		
	<b>Factors</b>	<ul style="list-style-type: none"> <li>• High feed and excessive honing of the cutting edge</li> <li>• Exceeded cutting tool's tool life (Too much wear and chipping)</li> </ul>
	<b>Solutions</b>	<ul style="list-style-type: none"> <li>• Reduce feed (Especially at the end of hole) and use a new drill.</li> <li>• Increase point angle or reduce honing.</li> </ul>
Flaking the end of the drilled hole		
	<b>Factors</b>	<ul style="list-style-type: none"> <li>• Machining of low toughness materials as cast iron</li> <li>• Rapid feed and excessive honing of the cutting edge</li> <li>• Exceeded cutting tool's tool life (Too much wear and chipping)</li> </ul>
	<b>Solutions</b>	<ul style="list-style-type: none"> <li>• Reduce the feed. (Especially at the end of hole)</li> <li>• Reduce honing on the cutting edge.</li> <li>• Use a new drill.</li> </ul>
Thermal deformation and oxidation of the end of the drilled hole		
	<b>Factors</b>	<ul style="list-style-type: none"> <li>• Rapid feed</li> <li>• Excessive cutting load</li> <li>• Lack of coolant</li> <li>• Exceeded cutting tool's tool life (Too much wear and chipping)</li> </ul>
	<b>Solutions</b>	<ul style="list-style-type: none"> <li>• Reduce the feed and honing on the cutting edge.</li> <li>• Use more coolant and use a new drill.</li> </ul>

## Solutions for troubles

↑ Increase ↓ Decrease ○ Use

Trouble	Designation	Solutions															
		Cutting conditions				Tool shape					Grade		The others				
		vc	fn	Coolant	fn (in the beginning)	Depth of cut	Relief angle	Point angle	Thinning angle	Honing	Flute width rate	Toughness	Hardness	Rigidity of machine	Chattering of machine	Fixing workpiece	Overhang
<b>Chipping</b>	<ul style="list-style-type: none"> <li>• Improper cutting conditions</li> <li>• Low rigidity of tool</li> <li>• Built-up edge</li> <li>• Improper grade</li> <li>• Chattering</li> </ul>	↓	↓	○			↓		↓	↑		↑		↑	↓	↑	↓
<b>Wear</b>	• Excessive cutting speed (wear on margin)	↓	↓	○								↑					
	• Low cutting speed (wear in the center of drill)	↑	↓	○								↑					
<b>Fracture</b>	<ul style="list-style-type: none"> <li>• Improper cutting conditions</li> <li>• Too much cutting load</li> <li>• Too long overhang</li> <li>• Less rigidity of machine</li> </ul>	↓	↓	○	↓	↓							↑		↑	↓	
<b>Poor chip evacuation</b>	• Improper cutting conditions		↓	○		↓					↑						
<b>Poor surface finish</b>	<ul style="list-style-type: none"> <li>• Built-up edge</li> <li>• Chattering</li> <li>• Improper cutting conditions</li> </ul>	↑	↓	○	↓			↓		↓			↑	↓	↑	↓	
<b>Poor accuracy of hole</b>	• Low cutting speed (wear in the center of drill)	↑	↓										↑	↓		↓	

# Special drill order form



## Hole type

- Blind hole
  Through hole


## Coolant type

- Internal
  External


## Special note

- Currently using tool:
- Current cutting condition
  - n (rpm) or vc (m/min):
  - vf (mm/min) or fn (mm/rev):
  - Depth of cut, ap (mm):
- Standard of measuring tool life:
- Currently using machine
  - Machining center:
  - General lathe:
  - CNC lathe:

## Shank type

-  Plain type
-  Flat type
-  Weldon type
-  Whistle notch type

# Insert



(mm)

Designation	Coated			ØD	h	t
	PC5300	PC5335	PC330P			
TPD 100B	●			10.0	5.5	3.5
105B	●			10.5	5.5	3.5
110B	●	●		11.0	5.8	3.5
115B	●			11.5	5.8	3.5
120B	●	●		12.0	6.3	3.5
125B	●	●		12.5	6.3	3.5
130B	●			13.0	6.5	4.0
135B	●			13.5	6.5	4.0
140B	●	●		14.0	6.8	4.0
145B	●	●		14.5	6.8	4.0
150B	●	●		15.0	7.0	4.0
155B	●	●		15.5	7.0	4.0
160B	●	●		16.0	7.7	5.5
165B	●	●		16.5	7.7	5.5
170B	●	●		17.0	7.9	5.5
175B	●	●		17.5	7.9	5.5
180B	●	●		18.0	8.1	6.0
185B	●	●		18.5	8.1	6.0
190B	●	●		19.0	8.3	6.0
195B	●			19.5	8.3	6.0
200B	●	●		20.0	9.7	6.5
205B	●			20.5	9.7	6.5
210B	●	●		21.0	9.4	6.5
215B	●			21.5	9.4	6.5
220B	●	●		22.0	9.6	7.0
225B	●			22.5	9.6	7.0
230B	●	●		23.0	9.8	7.0
235B	●			23.5	9.8	7.0
240B	●	●		24.0	10.7	7.5
245B	●			24.5	10.7	7.5
250B	●	●		25.0	10.9	7.5
255B	●			25.5	10.9	7.5
260B	●	●		26.0	11.0	8.5
265B	●			26.5	11.0	8.5
270B	●			27.0	11.8	8.5
275B	●			27.5	11.8	8.5
280B	●			28.0	12.6	9.5
285B	●			28.5	12.6	9.5
290B	●			29.0	12.9	9.5
295B	●			29.5	12.9	9.5
300B	●			30.0	13.0	10.0
305B	●			30.5	13.0	10.0
310B	●			31.0	13.2	10.0
315B	●			31.5	13.2	10.0
320B	●			32.0	13.4	10.0
325B	●			32.5	13.4	10.0


※ We can provide nonstock items with Ø10.00 - Ø32.99

●: Stock item

## Parts

Designation	Drill diameter ØD (mm)	Screw 	Wrench 	Torque (N·m)
TPD 100B - 129B	10.0 - 12.9	FTNB0209-P	TW06P	0.4
130B - 149B	13.0 - 14.9	FTNB02512-P	TW07S	0.8
150B - 179B	15.0 - 17.9	FTNB02514-P	TW07S	0.8
180B - 199B	18.0 - 19.9	FTNB0316-P	TW09S	1.2
200B - 239B	20.0 - 23.9	FTNB0319	TW09S	1.2
240B - 259B	24.0 - 25.9	FTNB03522	TW15S	3.0
260B - 279B	26.0 - 27.9	FTNB03524	TW15S	3.0
280B - 299B	28.0 - 29.9	FTNB0426	TW15S	3.0
300B - 329B	30.0 - 32.9	FTNB0528	TW20-100	4.0

# TPDB Plus (3D)




(mm)

Designation	Stock	ØD	Ød <sub>1</sub>	Ød <sub>2</sub>	ℓ <sub>1</sub>	ℓ <sub>2</sub>	L	Insert
TPDB 100-16-3-P	●	10.0 - 10.4	16	20	30.0	48	96.6	TPD100B - 104B
105-16-3-P	●	10.5 - 10.9	16	20	31.5	48	97.6	TPD105B - 109B
110-16-3-P	●	11.0 - 11.4	16	20	33.0	48	99.7	TPD110B - 114B
115-16-3-P	●	11.5 - 11.9	16	20	34.5	48	100.7	TPD115B - 119B
120-16-3-P	●	12.0 - 12.4	16	20	36.0	48	104.1	TPD120B - 124B
125-16-3-P	●	12.5 - 12.9	16	20	37.5	48	106.2	TPD125B - 129B
130-16-3-P	●	13.0 - 13.4	16	20	39.0	48	109.3	TPD130B - 134B
135-16-3-P	●	13.5 - 13.9	16	20	40.5	48	111.4	TPD135B - 139B
140-16-3-P	●	14.0 - 14.4	16	20	42.0	48	113.5	TPD140B - 144B
145-16-3-P	●	14.5 - 14.9	16	20	43.5	48	116.6	TPD145B - 149B
150-20-3-P	●	15.0 - 15.4	20	25	45.0	50	120.7	TPD150B - 154B
155-20-3-P	●	15.5 - 15.9	20	25	46.5	50	122.7	TPD155B - 159B
160-20-3-P	●	16.0 - 16.4	20	25	48.0	50	124.9	TPD160B - 164B
165-20-3-P	●	16.5 - 16.9	20	25	49.5	50	126.9	TPD165B - 169B
170-20-3-P	●	17.0 - 17.4	20	25	51.0	50	130.1	TPD170B - 174B
175-20-3-P	●	17.5 - 17.9	20	25	52.5	50	132.1	TPD175B - 179B
180-25-3-P	●	18.0 - 18.4	25	33	54.0	56	140.2	TPD180B - 184B
185-25-3-P	●	18.5 - 18.9	25	33	55.5	56	142.2	TPD185B - 189B
190-25-3-P	●	19.0 - 19.4	25	33	57.0	56	145.3	TPD190B - 194B
195-25-3-P	●	19.5 - 19.9	25	33	58.5	56	147.3	TPD195B - 199B
200-25-3-P	●	20.0 - 20.4	25	33	60.0	56	149.5	TPD200B - 204B
205-25-3-P	●	20.5 - 20.9	25	33	61.5	56	151.5	TPD205B - 209B
210-25-3-P	●	21.0 - 21.4	25	33	63.0	60	154.7	TPD210B - 214B
215-25-3-P	●	21.5 - 21.9	25	33	64.5	60	156.7	TPD215B - 219B
220-25-3-P	●	22.0 - 22.4	25	33	66.0	60	158.9	TPD220B - 224B
225-25-3-P	●	22.5 - 22.9	25	33	67.5	60	160.9	TPD225B - 229B
230-25-3-P	●	23.0 - 23.4	25	33	69.0	60	164.1	TPD230B - 234B
235-25-3-P	●	23.5 - 23.9	25	33	70.5	60	166.1	TPD235B - 239B
240-32-3-P	●	24.0 - 24.4	32	43	72.0	60	172.3	TPD240B - 244B
245-32-3-P	●	24.5 - 24.9	32	43	73.5	60	174.3	TPD245B - 249B
250-32-3-P	●	25.0 - 25.4	32	43	75.0	60	177.5	TPD250B - 254B
255-32-3-P	●	25.5 - 25.9	32	43	76.5	60	179.5	TPD255B - 259B
260-32-3-P	●	26.0 - 26.9	32	43	78.0	60	181.7	TPD260B - 269B
270-32-3-P	●	27.0 - 27.9	32	43	81.0	60	186.9	TPD270B - 279B
280-32-3-P	●	28.0 - 28.9	32	43	84.0	60	191.0	TPD280B - 289B
290-32-3-P	●	29.0 - 29.9	32	43	87.0	60	196.2	TPD290B - 299B
300-32-3-P	●	30.0 - 30.9	32	43	90.0	60	199.4	TPD300B - 309B
310-32-3-P	●	31.0 - 31.9	32	43	93.0	60	204.6	TPD310B - 319B
320-32-3-P	●	32.0 - 32.9	32	43	96.0	60	206.8	TPD320B - 329B

●: Stock item

# TPDB Plus (5D)




(mm)

Designation	Stock	ØD	Ød <sub>1</sub>	Ød <sub>2</sub>	ℓ <sub>1</sub>	ℓ <sub>2</sub>	L	Insert
TPDB 100-16-5-P	●	10.0 - 10.4	16	20	50.0	48	116.1	TPD100B - 104B
105-16-5-P	●	10.5 - 10.9	16	20	52.5	48	118.9	TPD105B - 109B
110-16-5-P	●	11.0 - 11.4	16	20	55.0	48	121.7	TPD110B - 114B
115-16-5-P	●	11.5 - 11.9	16	20	57.5	48	124.5	TPD115B - 119B
120-16-5-P	●	12.0 - 12.4	16	20	60.0	48	128.1	TPD120B - 124B
125-16-5-P	●	12.5 - 12.9	16	20	62.5	48	131.2	TPD125B - 129B
130-16-5-P	●	13.0 - 13.4	16	20	65.0	48	135.3	TPD130B - 134B
135-16-5-P	●	13.5 - 13.9	16	20	67.5	48	138.4	TPD135B - 139B
140-16-5-P	●	14.0 - 14.4	16	20	70.0	48	141.5	TPD140B - 144B
145-16-5-P	●	14.5 - 14.9	16	20	72.5	48	145.6	TPD145B - 149B
150-20-5-P	●	15.0 - 15.4	20	25	75.0	50	150.7	TPD150B - 154B
155-20-5-P	●	15.5 - 15.9	20	25	77.5	50	153.7	TPD155B - 159B
160-20-5-P	●	16.0 - 16.4	20	25	80.0	50	156.9	TPD160B - 164B
165-20-5-P	●	16.5 - 16.9	20	25	82.5	50	159.9	TPD165B - 169B
170-20-5-P	●	17.0 - 17.4	20	25	85.0	50	164.1	TPD170B - 174B
175-20-5-P	●	17.5 - 17.9	20	25	87.5	50	167.1	TPD175B - 179B
180-25-5-P	●	18.0 - 18.4	25	33	90.0	56	176.2	TPD180B - 184B
185-25-5-P	●	18.5 - 18.9	25	33	92.5	56	179.2	TPD185B - 189B
190-25-5-P	●	19.0 - 19.4	25	33	95.0	56	183.3	TPD190B - 194B
195-25-5-P	●	19.5 - 19.9	25	33	97.5	56	186.3	TPD195B - 199B
200-25-5-P	●	20.0 - 20.4	25	33	100.0	56	189.5	TPD200B - 204B
205-25-5-P	●	20.5 - 20.9	25	33	102.5	56	192.5	TPD205B - 209B
210-25-5-P	●	21.0 - 21.4	25	33	105.0	60	196.7	TPD210B - 214B
215-25-5-P	●	21.5 - 21.9	25	33	107.5	60	199.7	TPD215B - 219B
220-25-5-P	●	22.0 - 22.4	25	33	110.0	60	202.9	TPD220B - 224B
225-25-5-P	●	22.5 - 22.9	25	33	112.5	60	205.9	TPD225B - 229B
230-25-5-P	●	23.0 - 23.4	25	33	115.0	60	210.1	TPD230B - 234B
235-25-5-P	●	23.5 - 23.9	25	33	117.5	60	213.1	TPD235B - 239B
240-32-5-P	●	24.0 - 24.4	32	43	120.0	60	220.3	TPD240B - 244B
245-32-5-P	●	24.5 - 24.9	32	43	122.5	60	223.3	TPD245B - 249B
250-32-5-P	●	25.0 - 25.4	32	43	125.0	60	227.5	TPD250B - 254B
255-32-5-P	●	25.5 - 25.9	32	43	127.5	60	230.5	TPD255B - 259B
260-32-5-P	●	26.0 - 26.9	32	43	130.0	60	233.7	TPD260B - 269B
270-32-5-P	●	27.0 - 27.9	32	43	135.0	60	240.9	TPD270B - 279B
280-32-5-P	●	28.0 - 28.9	32	43	140.0	60	247.0	TPD280B - 289B
290-32-5-P	●	29.0 - 29.9	32	43	145.0	60	254.2	TPD290B - 299B
300-32-5-P	●	30.0 - 30.9	32	43	150.0	60	259.4	TPD300B - 309B
310-32-5-P	●	31.0 - 31.9	32	43	155.0	60	266.6	TPD310B - 319B
320-32-5-P	●	32.0 - 32.9	32	43	160.0	60	270.8	TPD320B - 329B

●: Stock item

# TPDB Plus (8D)




(mm)

Designation	Stock	ØD	Ød <sub>1</sub>	Ød <sub>2</sub>	ℓ <sub>1</sub>	ℓ <sub>2</sub>	L	Insert
TPDB 100-16-8-P	●	10.0 - 10.4	16	20	80	48	146.1	TPD100B - 104B
105-16-8-P	●	10.5 - 10.9	16	20	84	48	150.4	TPD105B - 109B
110-16-8-P	●	11.0 - 11.4	16	20	88	48	154.7	TPD110B - 114B
115-16-8-P	●	11.5 - 11.9	16	20	92	48	159.0	TPD115B - 119B
120-16-8-P	●	12.0 - 12.4	16	20	96	48	164.1	TPD120B - 124B
125-16-8-P	●	12.5 - 12.9	16	20	100	48	168.7	TPD125B - 129B
130-16-8-P	●	13.0 - 13.4	16	20	104	48	174.3	TPD130B - 134B
135-16-8-P	●	13.5 - 13.9	16	20	108	48	178.9	TPD135B - 139B
140-16-8-P	●	14.0 - 14.4	16	20	112	48	183.5	TPD140B - 144B
145-16-8-P	●	14.5 - 14.9	16	20	116	48	189.1	TPD145B - 149B
150-20-8-P	●	15.0 - 15.4	20	25	120	50	195.7	TPD150B - 154B
155-20-8-P	●	15.5 - 15.9	20	25	124	50	200.2	TPD155B - 159B
160-20-8-P	●	16.0 - 16.4	20	25	128	50	204.9	TPD160B - 164B
165-20-8-P	●	16.5 - 16.9	20	25	132	50	209.4	TPD165B - 169B
170-20-8-P	●	17.0 - 17.4	20	25	136	50	215.1	TPD170B - 174B
175-20-8-P	●	17.5 - 17.9	20	25	140	50	219.6	TPD175B - 179B
180-25-8-P	●	18.0 - 18.4	25	33	144	56	230.2	TPD180B - 184B
185-25-8-P	●	18.5 - 18.9	25	33	148	56	234.7	TPD185B - 189B
190-25-8-P	●	19.0 - 19.4	25	33	152	56	240.3	TPD190B - 194B
195-25-8-P	●	19.5 - 19.9	25	33	156	56	244.8	TPD195B - 199B
200-25-8-P	●	20.0 - 20.4	25	33	160	56	249.5	TPD200B - 204B
205-25-8-P	●	20.5 - 20.9	25	33	164	56	254.0	TPD205B - 209B
210-25-8-P	●	21.0 - 21.4	25	33	168	60	259.7	TPD210B - 214B
215-25-8-P	●	21.5 - 21.9	25	33	172	60	264.2	TPD215B - 219B
220-25-8-P	●	22.0 - 22.4	25	33	176	60	268.9	TPD220B - 224B
225-25-8-P	●	22.5 - 22.9	25	33	180	60	273.4	TPD225B - 229B
230-25-8-P	●	23.0 - 23.4	25	33	184	60	279.1	TPD230B - 234B
235-25-8-P	●	23.5 - 23.9	25	33	188	60	283.6	TPD235B - 239B
240-32-8-P	●	24.0 - 24.4	32	43	192	60	292.3	TPD240B - 244B
245-32-8-P	●	24.5 - 24.9	32	43	196	60	296.8	TPD245B - 249B
250-32-8-P	●	25.0 - 25.4	32	43	200	60	302.5	TPD250B - 254B
255-32-8-P	●	25.5 - 25.9	32	43	204	60	307.0	TPD255B - 259B
260-32-8-P	●	26.0 - 26.9	32	43	208	60	311.7	TPD260B - 269B
270-32-8-P	●	27.0 - 27.9	32	43	216	60	321.9	TPD270B - 279B
280-32-8-P	●	28.0 - 28.9	32	43	224	60	331.0	TPD280B - 289B
290-32-8-P	●	29.0 - 29.9	32	43	232	60	341.2	TPD290B - 299B
300-32-8-P	●	30.0 - 30.9	32	43	240	60	349.4	TPD300B - 309B
310-32-8-P	●	31.0 - 31.9	32	43	248	60	359.6	TPD310B - 319B
320-32-8-P	●	32.0 - 32.9	32	43	256	60	366.8	TPD320B - 329B

●: Stock item

# TPDB Plus (10D)




(mm)

Designation	Stock	ØD	Ød <sub>1</sub>	Ød <sub>2</sub>	ℓ <sub>1</sub>	ℓ <sub>2</sub>	L	Insert
TPDB 100-16-10-P	●	10.0 - 10.4	16	20	100	48	166.6	TPD100B - 104B
105-16-10-P	●	10.5 - 10.9	16	20	105	48	171.6	TPD105B - 109B
110-16-10-P	●	11.0 - 11.4	16	20	110	48	176.7	TPD110B - 114B
115-16-10-P	●	11.5 - 11.9	16	20	115	48	181.7	TPD115B - 119B
120-16-10-P	●	12.0 - 12.4	16	20	120	48	188.1	TPD120B - 124B
125-16-10-P	●	12.5 - 12.9	16	20	125	48	193.7	TPD125B - 129B
130-16-10-P	●	13.0 - 13.4	16	20	130	48	200.3	TPD130B - 134B
135-16-10-P	●	13.5 - 13.9	16	20	135	48	205.9	TPD135B - 139B
140-16-10-P	●	14.0 - 14.4	16	20	140	48	211.5	TPD140B - 144B
145-16-10-P	●	14.5 - 14.9	16	20	145	48	218.1	TPD145B - 149B
150-20-10-P	●	15.0 - 15.4	20	25	150	50	225.7	TPD150B - 154B
155-20-10-P	●	15.5 - 15.9	20	25	155	50	231.2	TPD155B - 159B
160-20-10-P	●	16.0 - 16.4	20	25	160	50	236.9	TPD160B - 164B
165-20-10-P	●	16.5 - 16.9	20	25	165	50	242.4	TPD165B - 169B
170-20-10-P	●	17.0 - 17.4	20	25	170	50	249.1	TPD170B - 174B
175-20-10-P	●	17.5 - 17.9	20	25	175	50	254.6	TPD175B - 179B
180-25-10-P	●	18.0 - 18.4	25	33	180	56	266.2	TPD180B - 184B
185-25-10-P	●	18.5 - 18.9	25	33	185	56	271.7	TPD185B - 189B
190-25-10-P	●	19.0 - 19.4	25	33	190	56	278.3	TPD190B - 194B
195-25-10-P	●	19.5 - 19.9	25	33	195	56	283.8	TPD195B - 199B
200-25-10-P	●	20.0 - 20.4	25	33	200	56	289.5	TPD200B - 204B
205-25-10-P	●	20.5 - 20.9	25	33	205	56	295.0	TPD205B - 209B
210-25-10-P	●	21.0 - 21.4	25	33	210	60	301.7	TPD210B - 214B
215-25-10-P	●	21.5 - 21.9	25	33	215	60	307.2	TPD215B - 219B
220-25-10-P	●	22.0 - 22.4	25	33	220	60	312.9	TPD220B - 224B
225-25-10-P	●	22.5 - 22.9	25	33	225	60	318.6	TPD225B - 229B
230-25-10-P	●	23.0 - 23.4	25	33	230	60	325.1	TPD230B - 234B
235-25-10-P	●	23.5 - 23.9	25	33	235	60	330.6	TPD235B - 239B
240-32-10-P	●	24.0 - 24.4	32	43	240	60	340.3	TPD240B - 244B
245-32-10-P	●	24.5 - 24.9	32	43	245	60	345.8	TPD245B - 249B
250-32-10-P	●	25.0 - 25.4	32	43	250	60	352.5	TPD250B - 254B
255-32-10-P	●	25.5 - 25.9	32	43	255	60	358.0	TPD255B - 259B
260-32-10-P	●	26.0 - 26.9	32	43	260	60	363.7	TPD260B - 269B
270-32-10-P	●	27.0 - 27.9	32	43	270	60	375.9	TPD270B - 279B
280-32-10-P	●	28.0 - 28.9	32	43	280	60	387.0	TPD280B - 289B
290-32-10-P	●	29.0 - 29.9	32	43	290	60	399.2	TPD290B - 299B
300-32-10-P	●	30.0 - 30.9	32	43	300	60	409.4	TPD300B - 309B
310-32-10-P	●	31.0 - 31.9	32	43	310	60	421.6	TPD310B - 319B
320-32-10-P	●	32.0 - 32.9	32	43	320	60	430.8	TPD320B - 329B

●: Stock item

# TPDB Plus (12D)



(mm)

Designation	Stock	ØD	Ød1	Ød2	l1	l2	L	Insert
TPDB 100-16-12-P	●	10.0 - 10.4	16	20	120	48	186.6	TPD100B - 104B
105-16-12-P	●	10.5 - 10.9	16	20	126	48	192.6	TPD105B - 109B
110-16-12-P	●	11.0 - 11.4	16	20	132	48	198.7	TPD110B - 114B
115-16-12-P	●	11.5 - 11.9	16	20	138	48	204.7	TPD115B - 119B
120-16-12-P	●	12.0 - 12.4	16	20	144	48	212.1	TPD120B - 124B
125-16-12-P	●	12.5 - 12.9	16	20	150	48	218.7	TPD125B - 129B
130-16-12-P	●	13.0 - 13.4	16	20	156	48	226.3	TPD130B - 134B
135-16-12-P	●	13.5 - 13.9	16	20	162	48	232.9	TPD135B - 139B
140-16-12-P	●	14.0 - 14.4	16	20	168	48	239.5	TPD140B - 144B
145-16-12-P	●	14.5 - 14.9	16	20	174	48	247.1	TPD145B - 149B
150-20-12-P	●	15.0 - 15.4	20	25	180	50	255.7	TPD150B - 154B
155-20-12-P	●	15.5 - 15.9	20	25	186	50	262.2	TPD155B - 159B
160-20-12-P	●	16.0 - 16.4	20	25	192	50	268.9	TPD160B - 164B
165-20-12-P	●	16.5 - 16.9	20	25	198	50	275.4	TPD165B - 169B
170-20-12-P	●	17.0 - 17.4	20	25	204	50	283.1	TPD170B - 174B
175-20-12-P	●	17.5 - 17.9	20	25	210	50	289.6	TPD175B - 179B
180-25-12-P	●	18.0 - 18.4	25	33	216	56	302.2	TPD180B - 184B
185-25-12-P	●	18.5 - 18.9	25	33	222	56	308.7	TPD185B - 189B
190-25-12-P	●	19.0 - 19.4	25	33	228	56	316.3	TPD190B - 194B
195-25-12-P	●	19.5 - 19.9	25	33	234	56	322.8	TPD195B - 199B
200-25-12-P	●	20.0 - 20.4	25	33	240	56	329.5	TPD200B - 204B
205-25-12-P	●	20.5 - 20.9	25	33	246	56	336.0	TPD205B - 209B
210-25-12-P	●	21.0 - 21.4	25	33	252	60	343.7	TPD210B - 214B
215-25-12-P	●	21.5 - 21.9	25	33	258	60	350.2	TPD215B - 219B
220-25-12-P	●	22.0 - 22.4	25	33	264	60	356.9	TPD220B - 224B
225-25-12-P	●	22.5 - 22.9	25	33	270	60	363.6	TPD225B - 229B
230-25-12-P	●	23.0 - 23.4	25	33	276	60	371.1	TPD230B - 234B
235-25-12-P	●	23.5 - 23.9	25	33	282	60	377.6	TPD235B - 239B
240-32-12-P	●	24.0 - 24.4	32	43	288	60	388.3	TPD240B - 244B
245-32-12-P	●	24.5 - 24.9	32	43	294	60	394.8	TPD245B - 249B
250-32-12-P	●	25.0 - 25.4	32	43	300	60	402.5	TPD250B - 254B
255-32-12-P	●	25.5 - 25.9	32	43	306	60	409.0	TPD255B - 259B
260-32-12-P	●	26.0 - 26.9	32	43	312	60	415.7	TPD260B - 269B
270-32-12-P	●	27.0 - 27.9	32	43	324	60	429.9	TPD270B - 279B
280-32-12-P	●	28.0 - 28.9	32	43	336	60	443.0	TPD280B - 289B
290-32-12-P	●	29.0 - 29.9	32	43	348	60	457.2	TPD290B - 299B
300-32-12-P	●	30.0 - 30.9	32	43	360	60	469.4	TPD300B - 309B
310-32-12-P	●	31.0 - 31.9	32	43	372	60	483.6	TPD310B - 319B
320-32-12-P	●	32.0 - 32.9	32	43	384	60	494.8	TPD320B - 329B

●: Stock item

# TPDB-F

## Code system

### 【Holder】



<b>TPD</b>	<b>B</b>	<b>220</b>	-	<b>25</b>	-	<b>1.5</b>	-	<b>F</b>
Top solid Piercing Drill	Insert type B: Blade type	Drill dia. 220: Ø22.0		Shank dia. 25: Ø25		Aspect ratio (L/D) 1.5D		Flat

### 【Insert】


<b>TPD</b>	<b>200</b>	<b>B</b>	-	<b>F</b>
Top solid Piercing Drill	Drill dia. 200: Ø20.0	Insert type B: Blade type		Cutting edge F: Flat FC: Flat Candle

## Features

- **High precision clamping system** - High precision clamping due to high precise grinding and auto-centering
- **Screw on clamping system** - Easy to replace insert
- **Cutting edge with 180° point angle** - Flat bottom machining
- **Low cutting load cutting edge** - Low cutting load and excellent chip control
- **High durability holder** - Improved wear resistance and durability with special surface treatment implementation
- **Holder with good chip evacuation** - Good chip evacuation and reduced cutting load with high helix angle



## Grade features





### PC5400

- PVD coating technology with high lubrication, built up edge resistance and chipping resistance
- Excellent chipping resistance due to high toughness coating with high adhesive strength
- Enhanced fracture resistance and stable machinability due to ultra-fine substrate with high toughness substrate

## Performance evaluation


### Precision

- **Workpiece** Alloy steel (42CrMo4, HRC22)
- **Cutting conditions**  $vc$  (m/min) = 70/90,  $fn$  (mm/rev) = 0.2/0.3,  $ap$  (mm) = 30, wet (20 bar)
- **Tools**
  - Insert TPDB200B-F (PC5400)
  - Holder TPDB200-25-1.5-F (Drill dia. =  $\varnothing 20$  mm)



▶ Cutting edge with low cutting load enhances high precision.

- **Workpiece** Alloy steel (42CrMo4, HRC22), Angled surface  $15^\circ$
- **Cutting conditions**  $vc$  (m/min) = 70,  $fn$  (mm/rev) = 0.21,  $ap$  (mm) = 20, wet (20 bar)
- **Tools**
  - Insert TPDB200B-F (PC5400)
  - Holder TPDB200-25-1.5-F (Drill dia. =  $\varnothing 20$  mm)




▶ Cutting edge with low cutting load enhances high precision.

# Performance evaluation

## Cutting load

- **Workpiece** Alloy steel (42CrMo4, HRC22)
- **Cutting conditions**
  - vc (m/min) = 70
  - fn (mm/rev) = 0.25
  - ap (mm) = 30
  - wet (20 bar)
- **Tools**
  - Insert** TPD200B-F (PC5400)
  - Holder** TPDB200-25-1.5-F (Drill dia. = Ø20 mm)




30% lower cutting load

- **TPDB-F**  
Average thrust 2392N
- **Competitor**  
Average thrust 3560N

► The sharp point shape reduces cutting load.


## Wear resistance

- **Workpiece** Alloy steel (42CrMo4, HRC22), Angled surface 15°
- **Cutting conditions**
  - vc (m/min) = 70
  - fn (mm/rev) = 0.21
  - ap (mm) = 20
  - wet (20 bar)
- **Tools**
  - Insert** TPD200B-F (PC5400)
  - Holder** TPDB200-25-1.5-F (Drill dia. = Ø20 mm)



[ TPDB-F ]

Excellent wear resistance and chipping resistance



[Competitor]

► Enhanced chipping resistance increases tool life due to stable wear on the cutting edge.

## Surface finish

- **Workpiece** Alloy steel (42CrMo4, HRC22), Angled surface 15°
- **Cutting conditions**
  - vc (m/min) = 90
  - fn (mm/rev) = 0.18
  - ap (mm) = 20
  - wet (20bar)
- **Tools**
  - Insert** TPD150B-F (PC5400)
  - Holder** TPDB150-16-1.5-F (Drill dia. = Ø15 mm)



[ TPDB-F ]

Enhanced surface finish



[Competitor]

► Low cutting load cutting edge ensures good surface finish.

## Chip control

- **Workpiece** Carbon steel (C45, HRC18)
- **Cutting conditions**
  - vc (m/min) = 90
  - fn (mm/rev) = 0.25
  - ap (mm) = 30
  - wet (20 bar)
- **Tools**
  - Insert** TPD200B-F (PC5400)
  - Holder** TPDB200-25-1.5-F (Drill dia. = Ø20 mm)



[ TPDB-F ]

Excellent chip control







[Competitor]

► Stable chip curling controls chip shape.





## Recommended cutting condition

Workpiece			Grade	vc (m/min)	Aspect ratio (L/D) = 1.5D Feed rate (mm/rev) per drill dia. (mm)	
ISO	Workpiece	HB			Ø14.0-Ø21.9	Ø22.0-Ø30.9
P Carbon steel	Low carbon steel (C10, C25 etc)	80-120	PC5400	80 (60-100)	0.2-0.3	0.22-0.32
	High carbon steel (C45, C50 etc)	180-280		70 (50-90)	0.2-0.3	0.22-0.32
P Alloy steel	Low alloy steel (18CrMo4, 42CrMo4 etc)	140-260		70 (50-90)	0.2-0.3	0.22-0.32
	High alloy steel (34CrMo4 etc)	260-320		60 (40-80)	0.2-0.3	0.22-0.32



Machining	Flat surface drilling	Angled surface drilling	Curved surface drilling	Plunging	Boring
Pic.					
1.5D	○	○	○	○	○

※ Please refer to the precaution in drilling in case of angled surface, curved surface drilling, plunging and boring.

## Precaution in drilling

Angled surface drilling	Curved surface drilling	Plunging	Boring
			
<ul style="list-style-type: none"> <li>Reduce the feed (fn) to 30% than general cutting conditions at the beginning and the end of angled surface. (In case, <math>\theta</math> is over <math>30^\circ</math>, reduce it to 50%.)</li> </ul>	<ul style="list-style-type: none"> <li>Reduce the feed (fn) to 30% than general cutting conditions at the beginning of curved surface. (In case, <math>\theta</math> is over <math>30^\circ</math>, reduce it to 50%.)</li> </ul>	<ul style="list-style-type: none"> <li>Reduce the depth of cut (ae) to shorter than 1/2 of drill diameter.</li> <li>In case, the depth of cut is longer than drill diameter, plunge with divided depth of cut.</li> </ul>	<ul style="list-style-type: none"> <li>Reduce the feed (fn) to 30% than general cutting conditions at the beginning of boring.</li> <li>Start with 2 mm stepping before boring to prevent long chip.</li> </ul>

# Insert



(mm)

Designation	Coated	ØD	h	t	a	b
	PC5400					
TPD	140B-F	14.0	8.75	4.0	0.065	0.055
	145B-F	14.5	8.75	4.0	0.065	0.055
	150B-F	15.0	9.25	4.0	0.065	0.055
	155B-F	15.5	9.25	4.0	0.065	0.055
	160B-F	16.0	10.25	5.5	0.065	0.055
	165B-F	16.5	10.25	5.5	0.065	0.055
	170B-F	17.0	10.75	5.5	0.065	0.055
	175B-F	17.5	10.75	5.5	0.065	0.055
	180B-F	18.0	11.75	6.0	0.065	0.055
	185B-F	18.5	11.75	6.0	0.065	0.055
	190B-F	19.0	12.25	6.0	0.065	0.055
	195B-F	19.5	12.25	6.0	0.065	0.055
	200B-F	20.0	12.75	6.5	0.065	0.055
	205B-F	20.5	12.75	6.5	0.065	0.055
	210B-F	21.0	13.25	6.5	0.065	0.055
	215B-F	21.5	13.25	6.5	0.065	0.055
	220B-F	22.0	13.75	7.0	0.065	0.055
	225B-F	22.5	13.75	7.0	0.065	0.055
	230B-F	23.0	14.25	7.0	0.065	0.055
	235B-F	23.5	14.25	7.0	0.065	0.055
	240B-F	24.0	14.75	7.5	0.065	0.055
	245B-F	24.5	14.75	7.5	0.065	0.055
	250B-F	25.0	15.25	7.5	0.065	0.055
	255B-F	25.5	15.25	7.5	0.065	0.055
	260B-F	26.0	15.75	8.5	0.065	0.055
	265B-F	26.5	15.75	8.5	0.065	0.055
	270B-F	27.0	16.75	8.5	0.065	0.055
	275B-F	27.5	16.75	8.5	0.065	0.055
	280B-F	28.0	17.75	9.5	0.065	0.055
	285B-F	28.5	17.75	9.5	0.065	0.055
290B-F	29.0	18.25	9.5	0.065	0.055	
295B-F	29.5	18.25	9.5	0.065	0.055	
300B-F	30.0	18.75	10.0	0.065	0.055	
305B-F	30.5	18.75	10.0	0.065	0.055	



※ We can provide nonstock items with Ø14.00 - Ø30.99

●: Stock item

## Parts

Designation	Drill diameter ØD (mm)	Screw 	Wrench 	Torque (N·m)	
TPD	140B-F ~ 149B-F	14.0 - 14.9	FTNB02512-P	TW07S	0.8
	150B-F ~ 179B-F	15.0 - 17.9	FTNB02514-P	TW07S	0.8
	180B-F ~ 199B-F	18.0 - 19.9	FTNB0316-P	TW09S	1.2
	200B-F ~ 239B-F	20.0 - 23.9	FTNB0319	TW09S	1.2
	240B-F ~ 259B-F	24.0 - 25.9	FTNB03522	TW15S	3.0
	260B-F ~ 279B-F	26.0 - 27.9	FTNB03524	TW15S	3.0
	280B-F ~ 299B-F	28.0 - 29.9	FTNB0426	TW15S	3.0
	300B-F ~ 309B-F	30.0 - 30.9	FTNB0528	TW20-100	4.0

# TPDB-F (1.5D)



(mm)

Designation	Stock	ØD	Ød1	Ød2	l1	l2	L	Insert
TPDB 140-16-1.5-F		14.0 - 14.4	16	20	28.0	48	86.0	TPD140B-F~TPD144B-F
145-16-1.5-F		14.5 - 14.9	16	20	29.0	48	87.0	TPD145B-F~TPD149B-F
150-20-1.5-F		15.0 - 15.4	20	25	30.0	50	93.0	TPD150B-F~TPD154B-F
155-20-1.5-F		15.5 - 15.9	20	25	31.0	50	94.0	TPD155B-F~TPD159B-F
160-20-1.5-F		16.0 - 16.4	20	25	32.0	50	95.0	TPD160B-F~TPD164B-F
165-20-1.5-F		16.5 - 16.9	20	25	33.0	50	96.0	TPD165B-F~TPD169B-F
170-20-1.5-F		17.0 - 17.4	20	25	34.0	50	97.0	TPD170B-F~TPD174B-F
175-20-1.5-F		17.5 - 17.9	20	25	35.0	50	98.0	TPD175B-F~TPD179B-F
180-20-1.5-F		18.0 - 18.4	20	25	36.0	50	99.0	TPD180B-F~TPD184B-F
185-20-1.5-F		18.5 - 18.9	20	25	37.0	50	100.0	TPD185B-F~TPD189B-F
190-25-1.5-F		19.0 - 19.4	25	33	38.0	56	101.0	TPD190B-F~TPD194B-F
195-25-1.5-F		19.5 - 19.9	25	33	39.0	56	102.0	TPD195B-F~TPD199B-F
200-25-1.5-F		20.0 - 20.4	25	33	40.0	56	116.0	TPD200B-F~TPD204B-F
205-25-1.5-F		20.5 - 20.9	25	33	41.0	56	117.0	TPD205B-F~TPD209B-F
210-25-1.5-F		21.0 - 21.4	25	33	42.0	56	118.0	TPD210B-F~TPD214B-F
215-25-1.5-F		21.5 - 21.9	25	33	43.0	56	119.0	TPD215B-F~TPD219B-F
220-25-1.5-F		22.0 - 22.4	25	33	44.0	56	120.0	TPD220B-F~TPD224B-F
225-25-1.5-F		22.5 - 22.9	25	33	45.0	56	121.0	TPD225B-F~TPD229B-F
230-25-1.5-F		23.0 - 23.4	25	33	46.0	56	122.0	TPD230B-F~TPD234B-F
235-25-1.5-F		23.5 - 23.9	25	33	47.0	56	123.0	TPD235B-F~TPD239B-F
240-32-1.5-F		24.0 - 24.4	32	43	48.0	60	128.5	TPD240B-F~TPD244B-F
245-32-1.5-F		24.5 - 24.9	32	43	49.0	60	129.5	TPD245B-F~TPD249B-F
250-32-1.5-F		25.0 - 25.4	32	43	50.0	60	130.5	TPD250B-F~TPD254B-F
255-32-1.5-F		25.5 - 25.9	32	43	51.0	60	131.5	TPD255B-F~TPD259B-F
260-32-1.5-F		26.0 - 26.4	32	43	52.0	60	132.5	TPD260B-F~TPD264B-F
265-32-1.5-F		26.5 - 26.9	32	43	53.0	60	133.5	TPD265B-F~TPD269B-F
270-32-1.5-F		27.0 - 27.4	32	43	54.0	60	134.5	TPD270B-F~TPD274B-F
275-32-1.5-F		27.5 - 27.9	32	43	55.0	60	135.5	TPD275B-F~TPD279B-F
280-32-1.5-F		28.0 - 28.4	32	43	56.0	60	136.5	TPD280B-F~TPD284B-F
285-32-1.5-F		28.5 - 28.9	32	43	57.0	60	137.5	TPD285B-F~TPD289B-F
290-32-1.5-F		29.0 - 29.4	32	43	58.0	60	138.5	TPD290B-F~TPD294B-F
295-32-1.5-F		29.5 - 29.9	32	43	59.0	60	139.5	TPD295B-F~TPD299B-F
300-32-1.5-F		30.0 - 30.4	32	43	60.0	60	140.5	TPD300B-F~TPD304B-F
305-32-1.5-F		30.5 - 30.9	32	43	61.0	60	141.5	TPD305B-F~TPD309B-F

●: Stock item

# TPDB-H

## Code system

### 【Holder】

<b>TPD</b>	<b>B</b>	<b>220</b>	-	<b>25</b>	-	<b>4</b>	-	<b>H</b>
Top solid Piercing Drill	Insert type B: Blade type	Drill dia. 220: Ø22.0		Shank dia. 25: Ø25		Aspect ratio (L/D) 3D, 4D, 8D ※ Flange shank (8F) for 8D		H-Beam



### 【Insert】

<b>TPD</b>	<b>200</b>	<b>B</b>	-	<b>H</b>
Top solid Piercing Drill	Drill dia. 200: Ø20.0	Insert type B: Blade type		H-Beam

## Features



- **High precision clamping system** - High precision clamping due highly precise grinding and auto-centering
- **Screw on clamping system** - Easy to replace insert
- **Edge design with excellent centering** - Low cutting load and good chip control
- **High durability holder** - Improved wear resistance and durability with special surface treatment implementation
- **Holder with good chip evacuation** - Good chip evacuation and reduced cutting load with high helix angle
- **Optimally designed oil hole** - Long tool life

## Insert features




- ↓ Applied Double R point edge design is optimized for excellent centering and stable machinability.
- ↓ Machinability and productivity are improved by minimizing both workpiece's bending and chipping at edge corner section.

## Holder features




[TPDB-H]



[Competitor]

Concentrated coolant injection on delicate cutting edge increases tool life.

## Grade features




### PC340Q new

- Application of high hardness lubricative PVD coating technology with excellent resistance on wear, built up edge and chipping.
- The special surface treatment improves chip evacuation and reduces wear on the rake face and relief face.
- High hardness ultra-fine substrate ensures high rigidity of cutting edge and good chipping resistance.

## Performance evaluation

### Chip control

- **Workpiece** Carbon steel (SS275, SM355A)
- **Cutting conditions** vc (m/min) = 80  
fn (mm/rev) = 0.2  
ap (mm) = 30  
wet
- **Tools** **Insert** TPD270B-H (PC340Q)  
**Holder** TPDB270-32-4-H  
(Drill dia. = Ø27 mm)



[SS275]



[SM355A]


Good chip control

### Wear resistance


- **Workpiece** Carbon steel (SS275)
- **Cutting conditions** vc (m/min) = 65, fn (mm/rev) = 0.25,  
ap (mm) = 30, wet
- **Tools** **Insert** TPD220B-H (PC340Q)  
**Holder** TPDB220-25-4-H  
(Drill dia. = Ø22 mm)



[SS275]





[SM355A]



Normal wear and still usable

## Workpiece and recommended cutting conditions

ISO	Workpiece		Workpiece materials	Grade	vc (m/min)	Aspect ratio (L/D) = 3D, 4D Feed rate (mm/rev) per drill dia. (mm)	
						Ø14.0-Ø21.0	Ø22.0-Ø30.0
P Carbon steel	H-Beam		SS275 (SS400*) SM355 (SM490*) SHN355 (SHN490*)	PC340Q	65 (60-75)	0.2-0.25	0.2-0.3
	Angle						
	Plate						
	Plate (Stacked)				60 (55-65)	0.15-0.25	0.15-0.25

\* : Old symbol

## Precaution in drilling

### Angled surface drilling




- The approach angle between drill and the workpiece at the beginning and the end should be less than 6°.
- Reduce the feed (f<sub>n</sub>) to 30-50% than general cutting conditions at the beginning and the end of angled surface.

### Stacked plates drilling



- Gap between the plates could make wrong chip evacuation causing fracture of the drill.
- Place stacked plates without any gap between each.

### Plunging



- Irregular cutting resistance in plunging could cause fracture and deformation of the drill.

### Boring



- Boring is not recommended due to wear and chipping in the corner of the insert.

## Application examples

### Carbon steel (SM355)



- **Cutting conditions**  $vc$  (m/min) = 60,  $fn$  (mm/rev) = 0.25,  $ap$  (mm) = 50, wet
- **Tools**  
**Insert** TPD240B-H (PC340Q)  
**Holder** TPDB240-32-3-H  
(Drill dia. = Ø24 mm)
- **Tool life** 60 m (Normal wear)

► Stable chip evacuation ensures tool life as 60 m in even machining with over 40 mm thickness.

### Carbon steel (SM355)



- **Cutting conditions**  $vc$  (m/min) = 70,  $fn$  (mm/rev) = 0.25,  $ap$  (mm) = 24, wet
- **Tools**  
**Insert** TPD270B-H (PC340Q)  
**Holder** TPDB270-32-3-H  
(Drill dia. = Ø27 mm)
- **Tool life** 40 m (Normal wear)

► High speed and high feed machining saves machining hours.

### Carbon steel (SS275)



- **Cutting conditions**  $vc$  (m/min) = 60,  $fn$  (mm/rev) = 0.20,  $ap$  (mm) = 12, wet
- **Tools**  
**Insert** TPD220B-H (PC340Q)  
**Holder** TPDB220-32-3-H  
(Drill dia. = Ø22 mm)
- **Tool life** 35 m (Normal wear)

► Stable machinability and long tool life are realized in machining various workpieces such as SM355, SS275, SHN355 etc.


### Carbon steel (SM355)



- **Cutting conditions**  $vc$  (m/min) = 65,  $fn$  (mm/rev) = 0.20,  $ap$  (mm) = 22, wet
- **Tools**  
**Insert** TPD240B-H (PC340Q)  
**Holder** TPDB240-32-3-H  
(Drill dia. = Ø24 mm)
- **Tool life** 40 m (Normal wear)

► Minimized cutting load in horizontal machining ensures high quality machining.

# Insert



(mm)

Designation	Coated	ØD	h	t
	PC340Q			
TPD	140B-H	14.0	10.0	4.0
	145B-H	14.5	10.0	4.0
	150B-H	15.0	10.5	4.0
	155B-H	15.5	10.5	4.0
	160B-H	16.0	11.5	5.5
	165B-H	16.5	11.5	5.5
	170B-H	17.0	12.0	5.5
	175B-H	17.5	12.0	5.5
	180B-H	18.0	13.0	6.0
	185B-H	18.5	13.0	6.0
	190B-H	19.0	13.5	6.0
	195B-H	19.5	13.5	6.0
	200B-H	20.0	14.5	6.5
	205B-H	20.5	14.5	6.5
	210B-H	21.0	15.0	6.5
	215B-H	21.5	15.0	6.5
	220B-H	22.0	15.5	7.0
	225B-H	22.5	15.5	7.0
	230B-H	23.0	16.0	7.0
	235B-H	23.5	16.0	7.0
	240B-H	24.0	16.5	7.5
	245B-H	24.5	16.5	7.5
	250B-H	25.0	17.0	7.5
	255B-H	25.5	17.0	7.5
	260B-H	26.0	17.5	8.5
	265B-H	26.5	17.5	8.5
	270B-H	27.0	18.5	8.5
	275B-H	27.5	18.5	8.5
	280B-H	28.0	19.5	9.5
	285B-H	28.5	19.5	9.5
290B-H	29.0	20.0	9.5	
295B-H	29.5	20.0	9.5	
300B-H	30.0	20.5	10.0	
305B-H	30.5	20.5	10.0	


※ We can provide nonstock items with Ø14.00 - Ø30.99

●: Stock item

## Parts

Designation	Drill diameter ØD (mm)	Screw 	Wrench 	Torque (N·m)
TPD	140B-H ~ 149B-H	FTNB02512-P	TW07S	0.8
	150B-H ~ 179B-H	FTNB02514-P	TW07S	0.8
	180B-H ~ 199B-H	FTNB0316-P	TW09S	1.2
	200B-H ~ 239B-H	FTNB0319	TW09S	1.2
	240B-H ~ 259B-H	FTNB03522	TW15S	3.0
	260B-H ~ 279B-H	FTNB03524	TW15S	3.0
	280B-H ~ 299B-H	FTNB0426	TW15S	3.0
	300B-H ~ 309B-H	FTNB0528	TW20-100	4.0

# TPDB-H (3D)




(mm)

Designation	Stock	ØD	Ød	l <sub>1</sub>	l <sub>2</sub>	L	Insert
TPDB 140-16-3-H		14.0 - 14.4	16	42	48	98.8	TPD140B-144B-H
145-16-3-H		14.5 - 14.9	16	43.5	48	100.8	TPD145B-149B-H
150-20-3-H		15.0 - 15.4	20	45	50	104.4	TPD150B-154B-H
155-20-3-H		15.5 - 15.9	20	46.5	50	106.4	TPD155B-159B-H
160-20-3-H		16.0 - 16.4	20	48	50	108.0	TPD160B-164B-H
165-20-3-H		16.5 - 16.9	20	49.5	50	110.0	TPD165B-169B-H
170-20-3-H		17.0 - 17.4	20	51	50	111.5	TPD170B-174B-H
175-20-3-H		17.5 - 17.9	20	52.5	50	113.5	TPD175B-179B-H
180-20-3-H		18.0 - 18.4	20	54	50	115.1	TPD180B-184B-H
185-20-3-H		18.5 - 18.9	20	55.5	50	117.1	TPD185B-189B-H
190-20-3-H		19.0 - 19.4	20	57	50	118.7	TPD190B-194B-H
195-20-3-H		19.5 - 19.9	20	58.5	50	120.7	TPD195B-199B-H
200-25-3-H		20.0 - 20.4	25	60	56	128.3	TPD200B-204B-H
205-25-3-H		20.5 - 20.9	25	61.5	56	130.3	TPD205B-209B-H
210-25-3-H		21.0 - 21.4	25	63	56	131.9	TPD210B-214B-H
215-25-3-H		21.5 - 21.9	25	64.5	56	133.9	TPD215B-219B-H
220-25-3-H		22.0 - 22.4	25	66	56	135.5	TPD220B-224B-H
225-25-3-H		22.5 - 22.9	25	67.5	56	137.5	TPD225B-229B-H
230-25-3-H		23.0 - 23.4	25	69	56	139.1	TPD230B-234B-H
235-25-3-H		23.5 - 23.9	25	70.5	56	141.1	TPD235B-239B-H
240-32-3-H		24.0 - 24.4	32	72	60	146.8	TPD240B-244B-H
245-32-3-H		24.5 - 24.9	32	73.5	60	148.8	TPD245B-249B-H
250-32-3-H		25.0 - 25.4	32	75	60	150.3	TPD250B-254B-H
255-32-3-H		25.5 - 25.9	32	76.5	60	152.3	TPD255B-259B-H
260-32-3-H		26.0 - 26.4	32	78	60	153.8	TPD260B-264B-H
265-32-3-H		26.5 - 26.9	32	79.5	60	155.8	TPD265B-269B-H
270-32-3-H		27.0 - 27.4	32	81	60	157.5	TPD270B-274B-H
275-32-3-H		27.5 - 27.9	32	82.5	60	159.5	TPD275B-279B-H
280-32-3-H		28.0 - 28.4	32	84	60	161.0	TPD280B-284B-H
285-32-3-H		28.5 - 28.9	32	85.5	60	163.0	TPD285B-289B-H
290-32-3-H		29.0 - 29.4	32	87	60	164.6	TPD290B-294B-H
295-32-3-H		29.5 - 29.9	32	88.5	60	166.6	TPD295B-299B-H
300-32-3-H		30.0 - 30.9	32	90	60	168.2	TPD300B-309B-H

● : Stock item

# TPDB-H (4D)




(mm)

Designation	Stock	ØD	Ød	l <sub>1</sub>	l <sub>2</sub>	L	Insert
TPDB 140-16-4-H		14.0 - 14.4	16	56	48	112.8	TPD140B-144B-H
145-16-4-H		14.5 - 14.9	16	58	48	115.3	TPD145B-149B-H
150-20-4-H		15.0 - 15.4	20	60	50	119.4	TPD150B-154B-H
155-20-4-H		15.5 - 15.9	20	62	50	121.9	TPD155B-159B-H
160-20-4-H		16.0 - 16.4	20	64	50	124.0	TPD160B-164B-H
165-20-4-H		16.5 - 16.9	20	66	50	126.5	TPD165B-169B-H
170-20-4-H		17.0 - 17.4	20	68	50	128.5	TPD170B-174B-H
175-20-4-H		17.5 - 17.9	20	70	50	131.0	TPD175B-179B-H
180-20-4-H		18.0 - 18.4	20	72	50	133.1	TPD180B-184B-H
185-20-4-H		18.5 - 18.9	20	74	50	135.6	TPD185B-189B-H
190-20-4-H		19.0 - 19.4	20	76	50	137.7	TPD190B-194B-H
195-20-4-H		19.5 - 19.9	20	78	50	140.2	TPD195B-199B-H
200-25-4-H		20.0 - 20.4	25	80	56	148.3	TPD200B-204B-H
205-25-4-H		20.5 - 20.9	25	82	56	150.8	TPD205B-209B-H
210-25-4-H		21.0 - 21.4	25	84	56	152.9	TPD210B-214B-H
215-25-4-H		21.5 - 21.9	25	86	56	155.4	TPD215B-219B-H
220-25-4-H		22.0 - 22.4	25	88	56	157.5	TPD220B-224B-H
225-25-4-H		22.5 - 22.9	25	90	56	160.0	TPD225B-229B-H
230-25-4-H		23.0 - 23.4	25	92	56	162.1	TPD230B-234B-H
235-25-4-H		23.5 - 23.9	25	94	56	164.6	TPD235B-239B-H
240-32-4-H		24.0 - 24.4	32	96	60	170.8	TPD240B-244B-H
245-32-4-H		24.5 - 24.9	32	98	60	173.3	TPD245B-249B-H
250-32-4-H		25.0 - 25.4	32	100	60	175.3	TPD250B-254B-H
255-32-4-H		25.5 - 25.9	32	102	60	177.8	TPD255B-259B-H
260-32-4-H		26.0 - 26.4	32	104	60	179.8	TPD260B-264B-H
265-32-4-H		26.5 - 26.9	32	106	60	182.3	TPD265B-269B-H
270-32-4-H		27.0 - 27.4	32	108	60	184.5	TPD270B-274B-H
275-32-4-H		27.5 - 27.9	32	110	60	187.0	TPD275B-279B-H
280-32-4-H		28.0 - 28.4	32	112	60	189.0	TPD280B-284B-H
285-32-4-H		28.5 - 28.9	32	114	60	191.5	TPD285B-289B-H
290-32-4-H		29.0 - 29.4	32	116	60	193.6	TPD290B-294B-H
295-32-4-H		29.5 - 29.9	32	118	60	196.1	TPD295B-299B-H
300-32-4-H		30.0 - 30.9	32	120	60	198.2	TPD300B-309B-H

●: Stock item

# TPDB-H (8D)



(mm)

Designation	Stock	ØD	Ød	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	L	Insert
TPDB	140-16-8F-H	14.0 - 14.4	16	50	112	48	176.3	TPD140B-144B-H
	145-16-8F-H	14.5 - 14.9	16	50	116	48	180.3	TPD145B-149B-H
	150-20-8F-H	15.0 - 15.4	20	50	120	50	187.4	TPD150B-154B-H
	155-20-8F-H	15.5 - 15.9	20	50	124	50	191.4	TPD155B-159B-H
	160-20-8F-H	16.0 - 16.4	20	50	128	50	196.5	TPD160B-164B-H
	165-20-8F-H	16.5 - 16.9	20	50	132	50	200.5	TPD165B-169B-H
	170-20-8F-H	17.0 - 17.4	20	50	136	50	205.5	TPD170B-174B-H
	175-20-8F-H	17.5 - 17.9	20	50	140	50	209.5	TPD175B-179B-H
	180-20-8F-H	18.0 - 18.4	20	50	144	50	215.6	TPD180B-184B-H
	185-20-8F-H	18.5 - 18.9	20	50	148	50	219.6	TPD185B-189B-H
	190-20-8F-H	19.0 - 19.4	20	50	152	50	223.7	TPD190B-194B-H
	195-20-8F-H	19.5 - 19.9	20	50	156	50	227.7	TPD195B-199B-H
	200-25-8F-H	20.0 - 20.4	25	50	160	56	237.8	TPD200B-204B-H
	205-25-8F-H	20.5 - 20.9	25	50	164	56	241.8	TPD205B-209B-H
	210-25-8F-H	21.0 - 21.4	25	50	168	56	245.9	TPD210B-214B-H
	215-25-8F-H	21.5 - 21.9	25	50	172	56	249.9	TPD215B-219B-H
	220-25-8F-H	22.0 - 22.4	25	50	176	56	254.0	TPD220B-224B-H
	225-25-8F-H	22.5 - 22.9	25	50	180	56	263.0	TPD225B-229B-H
	230-25-8F-H	23.0 - 23.4	25	50	184	56	267.1	TPD230B-234B-H
	235-25-8F-H	23.5 - 23.9	25	50	188	56	271.1	TPD235B-239B-H
	240-32-8F-H	24.0 - 24.4	32	50	192	60	279.3	TPD240B-244B-H
	245-32-8F-H	24.5 - 24.9	32	50	196	60	283.3	TPD245B-249B-H
	250-32-8F-H	25.0 - 25.4	32	50	200	60	287.3	TPD250B-254B-H
	255-32-8F-H	25.5 - 25.9	32	50	204	60	291.3	TPD255B-259B-H
	260-32-8F-H	26.0 - 26.4	32	50	208	60	295.3	TPD260B-264B-H
	265-32-8F-H	26.5 - 26.9	32	50	212	60	299.3	TPD265B-269B-H
	270-32-8F-H	27.0 - 27.4	32	50	216	60	303.5	TPD270B-274B-H
	275-32-8F-H	27.5 - 27.9	32	50	220	60	307.5	TPD275B-279B-H
	280-32-8F-H	28.0 - 28.4	32	50	224	60	313.5	TPD280B-284B-H
	285-32-8F-H	28.5 - 28.9	32	50	228	60	317.5	TPD285B-289B-H
290-32-8F-H	29.0 - 29.4	32	50	232	60	322.6	TPD290B-294B-H	
295-32-8F-H	29.5 - 29.9	32	50	236	60	326.6	TPD295B-299B-H	
300-32-8F-H	30.0 - 30.9	32	50	240	60	330.7	TPD300B-309B-H	

※ The maximum length of flute could be l<sub>2</sub>.

● : Stock item

[www.korloy.com](http://www.korloy.com)



Holystar B/D, 1350, Nambusunhwan-ro, Geumcheon-gu, Seoul, 08536, Korea  
Tel: +82-2-522-3181 Fax: +82-2-522-3184, +82-2-3474-4744 Web: [www.korloy.com](http://www.korloy.com) E-mail: [sales.khq@korloy.com](mailto:sales.khq@korloy.com)

### **KORLOY AMERICA**

620 Maple Avenue, Torrance, CA 90503, USA  
Tel: +1-310-782-3800 Toll Free: +1-888-711-0001 Fax: +1-310-782-3885  
E-mail: [sales.kai@korloy.com](mailto:sales.kai@korloy.com)

### **KORLOY INDIA**

Plot No. 415, Sector 8, IMT Manesar, Gurgaon 122051, Haryana, India  
Tel: +91-124-4391790 Fax: +91-124-4050032  
E-mail: [sales.kip@korloy.com](mailto:sales.kip@korloy.com)

### **KORLOY TURKEY**

Serifali Mahallesi, Burhan Sokak NO: 34  
Dudullu OSB/Umraniye/Istanbul, 34775, Turkey  
Tel: +90-216-415-8874 E-mail: [sales.ktl@korloy.com](mailto:sales.ktl@korloy.com)

### **KORLOY RUSSIA**

Krasivy Dom office No. 305, Bld. 5, Novovladykinskiy proezd 8, 127106,  
Moscow, Russia  
Tel: +7-495-280-1458 Fax: +7-495-280-1459 E-mail: [sales.krc@korloy.com](mailto:sales.krc@korloy.com)

### **KORLOY FACTORY QINGDAO**

Ground Dongjing Road 56(B) District Free Trade Zone. Qingdao, China  
Tel: +86-532-86959880 Fax: +86-532-86760651  
E-mail: [pro.kfq@korloy.com](mailto:pro.kfq@korloy.com)

### **KORLOY EUROPE**

Gablonzer Str. 25-27, 61440 Oberursel, Germany  
Tel: +49-6171-277-83-0 Fax: +49-6171-277-83-59  
E-mail: [sales.keg@korloy.com](mailto:sales.keg@korloy.com)

### **KORLOY BRASIL**

Av. Aruana 280, conj.12, WLC, Alphaville, Barueri,  
CEP06460-010, SP, Brasil  
Tel: +55-11-4193-3810 E-mail: [sales.kbl@korloy.com](mailto:sales.kbl@korloy.com)

### **KORLOY CHILE**

Av. Providencia 1650, Office 1009, 7500027  
Providencia-Santiago, Chile  
Tel: +56-229-295-490 E-mail: [sales.kcs@korloy.com](mailto:sales.kcs@korloy.com)

### **KORLOY MEXICO**

Queretaro, Mexico  
E-mail: [sales.kml@korloy.com](mailto:sales.kml@korloy.com)

### **KORLOY FACTORY INDIA**

Plot No. 415, Sector 8, IMT Manesar, Gurgaon 122051, Haryana, India  
Tel: +91-124-4391790 Fax: +91-124-4050032  
E-mail: [pro.kim@korloy.com](mailto:pro.kim@korloy.com)